Perfluorooctyltrimethoxysilane

Fluorinated silane for qualified low-surface-energy coatings and inorganic-surface modification.

CAS No.	EC / List No.	Transport
85857-16-5	288-657-1	Non-dangerous goods

Product Information

Fluorinated silane for qualified low-surface-energy coatings and inorganic-surface modification.

Specifications

Parameter	Specification
Appearance at 20°C	Colourless transparent liquid
Purity, supply specification	Purity >97.0%
Refractive index, n25D	1.3450 ±0.0050
Density, typical reference	1.45 g/mL at 25°C (typical reference)

Grade-specific supply limits. The agreed specification and batch COA govern delivery.

Typical Properties

Property	Typical Value
Molecular formula	C11H13F13O3Si
Molecular weight	468.28 g/mol

Applications

Water- and oil-repellent surface treatments: Ingredient for qualified surface-treatment processes.

Release and anti-fingerprint coatings: Fluorosilane raw material for selected release or anti-fingerprint coating development.

Inorganic surface and sol-gel modification: Ingredient for technically controlled inorganic-surface and sol-gel development.

Packaging / Storage

Item	Information
Packing	210 L drums (200 kg net) or 25 L containers (25 kg net)
Storage	Keep tightly sealed in dry compatible containers in a cool, ventilated area with secondary containment. Protect from moisture, heat, ignition sources and strong oxidizing agents. Restrict access and prevent any release to drains or water.
Handling	Use closed dry transfer with effective extraction. Avoid mist, vapour and skin or eye contact; wear task-qualified chemical-resistant gloves, goggles and protective clothing. Keep emergency washing facilities accessible. Assess the alcohol released during any hydrolysis.

Company Contact

Supplier	Hainan Zhongxin Chemical Co., Ltd. (ZXCHEM)
Shanghai office	Room 1001, Building A, Caohejing Center, No. 1520 Gumei Road, Xuhui District, Shanghai, China
Telephone / Email	+86-21-54265599 / sales@zxchem.com.cn
Website	www.zxchem.com